



MaxTens Steel Strapping Technical Specifications

Product Name	Width (mm)	Thickness (mm)	Finish	Winding	Break Strength(N/mm ²)	Target Weight (kg)
KD-5127	12.7	0.5	Blue/Paint	Ribbon/Oscillated	830/880	20~25/50
KD-6127	12.7	0.6	Blue/Paint	Ribbon/Oscillated	830/880	20~25/50
KD-5160	16.0	0.5	Blue/Paint	Ribbon/Oscillated	830/880	25/50
KD-6160	16.0	0.6	Blue/Paint	Ribbon/Oscillated	830/880	25/50
KD-5190	19.0	0.5	Blue/Paint	Ribbon/Oscillated	830/880	25/50
KD-6190	19.0	0.6	Blue/Paint	Ribbon/Oscillated	830/880	25/50
KD-8190	19.0	0.8	Blue/Paint	Ribbon/Oscillated	830/880	30/50
KD-9190	19.0	0.9	Blue/Paint	Ribbon/Oscillated	830/880	30/50
KD-7250	25.0	0.7	Blue/Paint	Ribbon	830/880/930	45
KD-8250	25.0	0.8	Blue/Paint	Ribbon	830/880/930	45
KD-9250	25.0	0.9	Blue/Paint	Ribbon	830/880/930	45
KD-7320	32.0	0.7	Blue/Paint/Zinc	Ribbon/Oscillated	830/880/930/980	50/200~450
KD-8320	32.0	0.8	Blue/Paint/Zinc	Ribbon/Oscillated	830/880/930/980	50/200~450
KD-9320	32.0	0.9	Blue/Paint/Zinc	Ribbon/Oscillated	830/880/930/980	50/200~450
KD-1320	32.0	1.0	Blue/Paint/Zinc	Ribbon/Oscillated	830/880/930/980	50/200~450